



Vehicle Standard (Australian Design Rule 57/00 – Special Requirements for L-Group Vehicles) 2006

I, JAMES ERIC LLOYD, Minister for Local Government, Territories and Roads,
determine this vehicle standard under subsection 7 (1) of the *Motor Vehicle Standards
Act 1989*.

Dated 5 July 2006

[Signed]

James Eric Lloyd

Minister for Local Government, Territories and Roads

CONTENTS

A. LEGISLATIVE PROVISIONS..... 3

B. SCOPE..... 3

C. APPLICABILITY AND IMPLEMENTATION..... 3

57.1. DEFINITIONS 4

57.2. REQUIREMENTS 4

57.3. ALTERNATIVE STANDARDS 9

A. LEGISLATIVE PROVISIONS**A.1. NAME OF STANDARD**

A.1.1. This Standard is the Vehicle Standard (Australian Design Rule 57/00 – Special Requirements for L-Group Vehicles) 2006.

A.1.2. This Standard may also be cited as Australian Design Rule 57/00 — Special Requirements for L-Group Vehicles.

A.2. COMMENCEMENT

A.2.1. This Standard commences on the day after it is registered.

A.3. REPEAL

A.3.1. This Standard repeals each vehicle standard with the name Australian Design Rule 57/00 — Special Requirements for L-Group Vehicles that is:

- (a) made under section 7 of the Motor Vehicle Standards Act 1989; and
- (b) in force at the commencement of this Standard.

A.3.2. This Standard also repeals each instrument made under section 7 of the Motor Vehicle Standards Act 1989 that creates a vehicle standard with the name Australian Design Rule 57/00 — Special Requirements for L-Group Vehicles, if there are no other vehicle standards created by that instrument, or amendments to vehicle standards made by that instrument, that are still in force at the commencement of this Standard.

B. SCOPE

B.1. The function of this national standard is to specify special requirements for the construction of L-Group vehicles.

B.2. They must also comply with all requirements for L-group vehicles as set out in individual ADRs.

C. APPLICABILITY AND IMPLEMENTATION**C.1. Applicability Summary**

C.1.1. This national standard applies to the design and construction of vehicle as set out in the table below.

C.1.2. Applicability Table

Vehicle Category	ADR Category Code*	UNECE Category Code*	Manufactured on or After	Acceptable Prior Rules
Moped 2 wheels	LA	L1	1 July 1998	Nil
Moped 3 wheels	LB	L2	Not applicable	
Motor cycle	LC	L3	1 July 1998	Nil
Motor cycle and sidecar	LD	L4	1 July 1998	Nil
Motor tricycle	LE	L5	Not applicable	
Passenger car	MA	M1	Not applicable	
Forward-control passenger vehicle	MB	M1	Not applicable	
Off-road passenger vehicle	MC	M1	Not applicable	
Light omnibus	MD	M2	Not applicable	
Heavy omnibus	ME	M3	Not applicable	
Light goods vehicle	NA	N1	Not applicable	
Medium goods vehicle	NB	N2	Not applicable	
Heavy goods vehicle	NC	N3	Not applicable	
Very light trailer	TA	O1	Not applicable	
Light trailer	TB	O2	Not applicable	
Medium trailer	TC	O3	Not applicable	
Heavy trailer	TD	O4	Not applicable	

57.1. DEFINITIONS

57.1.1. Refer to Vehicle Standard (Australian Design Rule Definitions and Vehicle Categories) 2005.

57.2. REQUIREMENTS

57.2.1. Side-cars

57.2.1.1. A side-car must not be so attached to a vehicle nor must it be of such mass or dimensions as to prevent the driver from safely driving the vehicle or from having a sufficient view to the front, rear and either side of the vehicle to enable the vehicle to be driven with safety.

57.2.1.2. A side-car must not be attached to the right-hand side of a vehicle.

57.2.2. Steering Gear and Handlebars

57.2.2.1. Handlebars must extend not less than 250 mm nor more than 450 mm on each side of the centreline of the vehicle.

57.2.2.2. The height of the lowest part of the handgrip above the lowest part of the upper surface of the driver's seat must not exceed 380 mm.

57.2.2.3. All steering gear and steering gear connections must be so designed to eliminate accidental detachment or over-locking.

* The category code may also be in the format L₁, L_A etc.

- 57.2.2.4. The horizontal distance measured from the mid-point between the head stem bearings where the head stem is the steering pivot point, to a point vertically above the centre of the front wheel must not exceed 550 mm.
- 57.2.2.5. The handlebars must be symmetrical on either side of the front wheel and steering head assembly.
- 57.2.3. Operation and Location of Controls
- 57.2.3.1. Column 1 of Table 1 indicates whether controls are mandatory (M) or optional (O). The designation M+ indicates that applicability depends on the vehicle's design.
- 57.2.3.1.1. In any case where an item of equipment listed in Column 2 of Table 1 is provided, the control for such item must be located as specified in Column 3 of Table 1 and mode of control operation must be as specified in Column 4 of Table 1.
- 57.2.3.1.2. Each of the following controls located on the right handlebar must be operable throughout its full range by the driver's right hand without removal of the hand from the throttle:
- 57.2.3.1.2.1. Hand lever controlling front wheel brake;
- 57.2.3.1.2.2. Direction indicator control (if fitted to right handlebar); and
- 57.2.3.1.2.3. Supplemental Engine Stop.
- 57.2.3.1.3. Each of the following controls located on the left handlebar must be operable throughout its full range by the driver's left hand without removal of the hand from the handgrip:
- 57.2.3.1.3.1. Hand lever controlling the clutch;
- 57.2.3.1.3.2. Direction indicator control (if fitted to left handlebar);
- 57.2.3.1.3.3. Horn button; and
- 57.2.3.1.3.4. Headlamp main/dipped beam control.
- 57.2.3.1.4. In the case where a vehicle is equipped with self-proportioning or anti-lock braking devices utilising a single control for front and rear brakes, the requirements for location and operation of the control must be as for a rear brake control.
- 57.2.3.2. Visual Indicator Display and Illumination Requirements
- In any case where a visual indicator listed in Column 1 of Table 2 is provided, the information which is displayed must be visible to the seated driver under daylight conditions. Display illumination and operation of display illumination must be as specified in Column 2 of Table 2.
- 57.2.3.3. Control and Visual Indicator Display Identification Requirements
- In any case where an item of equipment or visual indicator listed in Column 1 of Table 3 is provided, the control or display for such item must be identified by the word or words shown in Column 2 of Table 3. Control positions must be identified to signify the function performed at that control position, by at least the data specified in Column 3. The items of equipment or visual indicators listed in Table 3, other than the Manual Fuel Shut-off Control; the Manual Choke; and the Ignition Switch must be

visible to the seated driver and the control or display identification must be legible to the seated driver.

- 57.2.3.3.1. In clause 57.2.3.3 above, as an alternative to using the words in columns 2 and 3 of table 3, the use of equivalent ISO symbols to identify a control and signify the function performed at the control is permissible.
- 57.2.3.4. “Clockwise” and “counter-clockwise” as specified in the following Tables refer to opposing directions of rotation around the following axes, as applicable:
 - 57.2.3.4.1. the operational axis of the ignition control viewed from in front of the ignition key opening; or
 - 57.2.3.4.2. the axis of the right handlebar on which the twist grip throttle is located, viewed from the outer end of that handlebar.

TABLE 1
CONTROL LOCATION AND OPERATION REQUIREMENTS

Column 1 Mandatory operation or optional	Column 2 Equipment or control	Column 3 Control location	Column 4 Control
M ⁺	Manual clutch (handlever) or combined clutch and gear change	Left handlebar	Squeeze to disengage clutch
O	Foot-operated gear change pedal	Left foot control	Up from first gear position to select lower numerical gear ratios commonly referred to as "higher gears") and down to select higher numerical gear ratios (commonly referred to as "lower gears")
M	Headlamp main/dipped beam control	Left handlebar	Up for main beam, down for dipped beam. In the case where the control is combined with the headlamp on-off control, means must be provided to prevent inadvertent actuation of the "off" functions.
M	Horn	Left handlebar	Push to activate.
M	Direction indicator lamps	Left or right handlebar	-----
O	Ignition switch	-----	Off-counterclockwise from other positions.
O	Manual only fuel shut-off control	-----	(1) Off-forward; On-downward. Reserve (if provided) - On-upward; or (2) as per FMVSS 123.
M	Twist grip throttle	Right handlebar	Self-closing in a clockwise direction to idle position after release of hand.
M	Supplemental Engine Stop	Right handlebar	A thumb-operated device to stop engine.
M	Front wheel brake hand lever	Right handlebar	Squeeze to activate.
M	Rear wheel brake - motor cycles - motor cycles equipped with automatic transmission	Right foot control As above; or Left handlebar	Depress to activate Squeeze to activate.
M	Rear wheel brake - mopeds - mopeds equipped with automatic transmission	Right foot control As above; or Left handlebar	Depress to activate Squeeze to activate.

⁺ **Note:** Indicates dependent on vehicle design

TABLE 2
VISUAL INDICATOR DISPLAY ILLUMINATION REQUIREMENTS

Column 1	Column 2
Visual Indicator Display	Illumination
Speedometer	Illuminated whenever the head lamp is illuminated.
Neutral indicator	Green display lamp illuminated when the gear selector is in the neutral position.
Main beam indicator - LC, LD only (LA - Dipped Beam Only)	Blue display lamp illuminated whenever the headlamp is illuminated and the headlamp main/dipped beam control is in the main beam mode.

TABLE 3
CONTROL AND VISUAL INDICATORS
DISPLAY IDENTIFICATION REQUIREMENTS

Column 1	Column 2	Column 3
Control or Display	Identification of Control or Display	Identification at Position of Control
Appropriate or Display		
Ignition Switch	—	Off
Supplemental Engine Stop	Engine stop	Off, Run
Manual Choke	Choke	-----
Electric Starter	-----	Start
Headlamp Main/Dipped Beam Control	Lights	Hi, Lo
Horn	Horn	-----
Direction Indicator	Turn	L,R
Main Beam or High Beam Indicator	Main Beam or High beam	-----
Tachometer	r/min; rpm; RPM; or min ⁻¹	-----
Fuel Tank Shut-Off Control	Fuel	Off, On, Res.
Neutral Indicator	Neutral	-----
Speedometer	km/h	Major gradations marked at 10 km/h intervals

57.2.4. Transmission Requirement

All vehicles equipped with manual transmission which are powered by an internal combustion engine, must be so designed to allow the transmission to be disengaged by the driver at any engine speed.

57.2.5. Electrical Generator

All vehicles must be fitted with a generator capable of maintaining a continuous supply of electrical energy required for continuous operation of the ignition and lighting systems when stationary with the engine operating at idle. The supply of electrical energy must be not less than that required for continuous operation of all lamps installed, except front/rear fog lamp(s), reversing lamp, 'Internal Lamp' and 'Search Lamp'.

57.2.6. Foot Rests

Every vehicle must be fitted with foot rests for the driver and also for the passenger if a seating position for passenger is provided.

57.2.7. Stands

57.2.7.1. All LA and LC group vehicles must be equipped with a stand capable of holding the vehicle in a substantially upright stable position. The stand may be of the side or centre type and must be equipped with a spring or other device capable of holding it clear of the road under normal operating conditions.

57.2.7.2. In the case of vehicles so equipped with a side stand, the side stand must either:

57.2.7.2.1. automatically fold back into the closed or riding position,

57.2.7.2.1.1. when the vehicle is returned to the normal vertical position for riding; or

57.2.7.2.1.2. as a result of the vehicle being moved forward by a deliberate action of the rider; or

57.2.7.2.1.3. without disturbing the equilibrium of the vehicle, if the side stand comes into contact with the road while the vehicle is moving; or

57.2.7.2.2. be connected to the ignition system in such a manner that the ignition system can only be activated when the side stand is in the closed or riding position; or

57.2.7.2.3. be connected to an audible signal and a warning lamp, visible to the rider in the normal riding position, which are activated if the ignition is switched on and the side stand is not in the closed or riding position; or

57.2.7.2.4. be connected in such a manner so that the vehicle cannot be operated under its own power unless it is retracted.

57.2.8. Chain Guards

Every vehicle, where the chain transmits engine power must, if the frame or any other equipment does not provide such protection, be fitted with a chain guard which must provide protection from the front sprocket and at least the upper free-run of the drive chain to a point not less than 300 mm to the rear of the rearmost footrest or to a point vertically above the centre of the rear drive sprocket.

57.3. ALTERNATIVE STANDARDS

The technical requirements of ECE R 60/00 "Motorcycle/moped controls" are to be deemed to be equivalent to the technical requirements for:

Operation & Location of Controls ;

Visual Indicator Display & Illumination Requirements; and

Control & Visual Indicator Display Identification requirements, of this rule.